

Activated carbon Cylinder

APPLICATIONS

- Removal of odors and gases

ADVANTAGES

- Compact and affordable
- Easy to place cartridges in frame thanks to bayonet connection
- Solid construction
- Cartridges can be filled with various types of filter media

SPECIFICATIONS

- Cartridge: Double-walled perforated galvanized steel sleeve. Also available in stainless steel and plastic
- Medium: standard activated carbon. Impregnated carbon or chemical filter medium on request
- Seal: Flat neoprene
- Maximum temperature carbon: 50° Celsius
- Maximum relative humidity carbon: 70%



ARTICLE NUMBER	LENGTH MM.	DIAMETER MM.	MEDIA BED THICKNESS MM.	WEIGHT OF CARBON (KG)	WEIGHT (KG)	FLANGE	FLOW RATE M3/H	CARBON TYPE	TYPE
99010003	250	145	25	1,2	1,8	ON DEMAND	75	PELLETISED	CAN 1500
99010002	450	145	25	2,2	2,8	ON DEMAND	156	PELLETISED	CAN 2600
	400	140	35	2,3	3,1	ON DEMAND	175	PELLETISED	CAN 4000
99010040	410	160	35	2,6	4	ON DEMAND	200	PELLETISED	CAN 4100
99010128	600	145	25	3	3,8	ON DEMAND	200	PELLETISED	CAN 9000

Alternative sizes on request