

Pocket filter

Synthetic ePM2,5 70%

APPLICATIONS

- Fine filtration for air handling units and prefiltration for (H) EPA filters

ADVANTAGES

- High dust-holding capacity
- Low pressure drop
- Conical self-supporting bags
- Applicable within the food industry
- Eurovent certified through the manufacturer

SPECIFICATIONS

- Media: Synthetic with progressive build-up
- Frame: Galvanized steel, also available in wood and plastic
- Recommended final resistance: 250 Pa
- Maximum continuous temperature: 80° Celsius
- Maximum relative humidity: 100%



ARTICLE NUMBER	WIDTH MM.	HEIGHT MM.	LENGTH MM.	NUMBER OF POCKETS	ISO 16890	EN 779	FLOW RATE M3/H	INITIAL RESISTANCE	ENERGY USAGE
01010016	287	287	360	4	ePM2,5 70%	F7	850	120	
01010015	287	592	360	4	ePM2,5 70%	F7	1700	120	
01010974	287	892	360	4	ePM2,5 70%	F7	2550	120	
01010018	490	592	360	6	ePM2,5 70%	F7	2800	120	
01011097	490	892	360	6	ePM2,5 70%	F7	4200	120	
01010014	592	287	360	8	ePM2,5 70%	F7	1700	120	
01010017	592	490	360	8	ePM2,5 70%	F7	2800	120	
01010013	592	592	360	8	ePM2,5 70%	F7	3400	120	
01011171	592	892	360	8	ePM2,5 70%	F7	5100	120	

Alternative sizes on request

ARTICLE NUMBER	WIDTH MM.	HEIGHT MM.	LENGTH MM.	NUMBER OF POCKETS	ISO 16890	EN 779	FLOW RATE M3/H	INITIAL RESISTANCE	ENERGY USAGE
01010010	287	287	500	4	ePM2,5 70%	F7	850	115	>2000
01010009	287	592	500	4	ePM2,5 70%	F7	1700	115	>2000
01010975	287	892	500	4	ePM2,5 70%	F7	2550	115	>2000
01010012	490	592	500	6	ePM2,5 70%	F7	2800	115	>2000
	490	892	500	6	ePM2,5 70%	F7	4200	115	>2000
01010008	592	287	500	8	ePM2,5 70%	F7	1700	115	>2000
01010011	592	490	500	8	ePM2,5 70%	F7	2800	115	>2000
01010007	592	592	500	8	ePM2,5 70%	F7	3400	115	>2000
01011172	592	892	500	8	ePM2,5 70%	F7	5100	115	>2000
01010004	287	287	600	4	ePM2,5 70%	F7	850	103	1555
01010003	287	592	600	4	ePM2,5 70%	F7	1700	103	1555
01010977	287	892	600	4	ePM2,5 70%	F7	2550	103	1555
01010006	490	592	600	6	ePM2,5 70%	F7	2800	103	1555
01011099	490	892	600	6	ePM2,5 70%	F7	4200	103	1555
01010002	592	287	600	8	ePM2,5 70%	F7	1700	103	1555
01010005	592	490	600	8	ePM2,5 70%	F7	2800	103	1555
01010001	592	592	600	8	ePM2,5 70%	F7	3400	103	1555
01011174	592	892	600	8	ePM2,5 70%	F7	5100	103	1555

Alternative sizes on request

Pocket filter

Synthetic ePM10 55%

APPLICATIONS

- Medium (pre)filtration for air handling units and air inlet grilles
- Exhaust air filtration

ADVANTAGES

- High dust-holding capacity
- Low pressure drop
- Conical self-supporting bags
- Applicable within the food industry
- Eurovent certified through the manufacturer

SPECIFICATIONS

- Media: Synthetic with progressive build-up
- Frame: Galvanized steel, also available in wood and plastic
- Recommended final resistance: 250 Pa
- Maximum continuous temperature: 80° Celsius
- Maximum relative humidity: 100%



ARTICLE NUMBER	WIDTH MM.	HEIGHT MM.	LENGTH MM.	NUMBER OF POCKETS	ISO 16890	EN 779	FLOW RATE M3/H	INITIAL RESISTANCE	ENERGY USAGE
01010034	287	287	360	3	ePM10 55%	M5	850	55	> 1100
01010033	287	592	360	3	ePM10 55%	M5	1700	55	> 1100
01010521	287	892	360	3	ePM10 55%	M5	2550	55	> 1100
01010036	490	592	360	5	ePM10 55%	M5	2800	55	> 1100
01010582	490	892	360	5	ePM10 55%	M5	4200	55	> 1100
01010032	592	287	360	6	ePM10 55%	M5	1700	55	> 1100
01010035	592	490	360	6	ePM10 55%	M5	2800	55	> 1100
01010031	592	592	360	6	ePM10 55%	M5	3400	55	> 1100
01010619	592	892	360	6	ePM10 55%	M5	5100	55	> 1100

Alternative sizes on request

ARTICLE NUMBER	WIDTH MM.	HEIGHT MM.	LENGTH MM.	NUMBER OF POCKETS	ISO 16890	EN 779	FLOW RATE M3/H	INITIAL RESISTANCE	ENERGY USAGE
01010028	287	287	500	3	ePM10 55%	M5	850	53	>1200
01010027	287	592	500	3	ePM10 55%	M5	1700	53	>1200
01010522	287	892	500	3	ePM10 55%	M5	2550	53	>1200
01010030	490	592	500	5	ePM10 55%	M5	2800	53	>1200
01010583	490	892	500	5	ePM10 55%	M5	4200	53	>1200
01010026	592	287	500	6	ePM10 55%	M5	1700	53	>1200
01010029	592	490	500	6	ePM10 55%	M5	2800	53	>1200
01010025	592	592	500	6	ePM10 55%	M5	3400	53	>1200
01010620	592	892	500	6	ePM10 55%	M5	5100	53	>1200
01010022	287	287	600	3	ePM10 55%	M5	850	40	1458
01010021	287	592	600	3	ePM10 55%	M5	1700	40	1458
01010524	287	892	600	3	ePM10 55%	M5	2550	40	1458
01010024	490	592	600	5	ePM10 55%	M5	2800	40	1458
01010585	490	892	600	5	ePM10 55%	M5	4200	40	1458
01010020	592	287	600	6	ePM10 55%	M5	1700	40	1458
01010023	592	490	600	6	ePM10 55%	M5	2800	40	1458
01010019	592	592	600	6	ePM10 55%	M5	3400	40	1458
01010623	592	892	600	6	ePM10 55%	M5	5100	40	1458

Alternative sizes on request

Pocket filter

Synthetic Coarse 65%

APPLICATIONS

- Coarse (pre)filtration for air handling units and air inlet grilles
- Exhaust air filtration

ADVANTAGES

- High dust-holding capacity
- Low pressure drop
- Conical self-supporting bags
- Applicable within the food industry
- Eurovent certified through the manufacturer

SPECIFICATIONS

- Media: Synthetic with progressive build-up
- Frame: Galvanized steel, also available in wood and plastic
- Recommended final resistance: 250 Pa
- Maximum continuous temperature: 80° Celsius
- Maximum relative humidity: 100%



ARTICLE NUMBER	WIDTH MM.	HEIGHT MM.	LENGTH MM.	NUMBER OF POCKETS	ISO 16890	EN 779	FLOW RATE M3/H	INITIAL RESISTANCE	ENERGY USAGE
01010052	287	287	360	3	Coarse 65%	G4	850	37	
01010051	287	592	360	3	Coarse 65%	G4	1700	37	
01010238	287	892	360	3	Coarse 65%	G4	2550	37	
01010054	490	592	360	5	Coarse 65%	G4	2800	37	
01010283	490	892	360	5	Coarse 65%	G4	4200	37	
01010050	592	287	360	6	Coarse 65%	G4	1700	37	
01010053	592	490	360	6	Coarse 65%	G4	2800	37	
01010049	592	592	360	6	Coarse 65%	G4	3400	37	
01010313	592	892	360	6	Coarse 65%	G4	5100	37	

Alternative sizes on request

ARTICLE NUMBER	WIDTH MM.	HEIGHT MM.	LENGTH MM.	NUMBER OF POCKETS	ISO 16890	EN 779	FLOW RATE M3/H	INITIAL RESISTANCE	ENERGY USAGE
01010046	287	287	500	3	Coarse 65%	G4	850		
01010045	287	592	500	3	Coarse 65%	G4	1700		
01010239	287	892	500	3	Coarse 65%	G4	2550		
01010048	490	592	500	5	Coarse 65%	G4	2800		
01010284	490	892	500	5	Coarse 65%	G4	4200		
01010044	592	287	500	6	Coarse 65%	G4	1700		
01010047	592	490	500	6	Coarse 65%	G4	2800		
01010043	592	592	500	6	Coarse 65%	G4	3400		
01010314	592	892	500	6	Coarse 65%	G4	5100		
01010040	287	287	600	3	Coarse 65%	G4	850	30	
01010039	287	592	600	3	Coarse 65%	G4	1700	30	
01010240	287	892	600	3	Coarse 65%	G4	2550	30	
01010042	490	592	600	5	Coarse 65%	G4	2800	30	
01010285	490	892	600	5	Coarse 65%	G4	4200	30	
01010038	592	287	600	6	Coarse 65%	G4	1700	30	
01010041	592	490	600	6	Coarse 65%	G4	2800	30	
01010037	592	592	600	6	Coarse 65%	G4	3400	30	
01010315	592	892	600	6	Coarse 65%	G4	5100	30	

Alternative sizes on request